

# AIR KNOCKER!!

Solve the blockage

Clinging and compacted materials are broken by the impact force.



OPECON 「AOC-1B」

## Feature

- (1) Impact force can be adjusted by supply air pressure.
- (2) Relay piping function allows operation of multiple knockers by one valve.
- (3) Low air consumption.

Special Control Panel for Air Knocker

**OPECON 「AOC-1B」**

Stroke cycle can be adjusted.

Power supply is not necessary.

Model	Working pressure	Stroke cycle	Air consumption	Stroke energy	Impact force		Weight
	(Bar)				(Time/min)	(ft <sup>3</sup> /time)	
RKV 30PA	3~7	1~60	0.002~0.004	4.05~9.66	12.3~18.8	~1.0 (lb)	2.9
RKV 40PA			0.005~0.013	6.80~16.45	20.7~32.0	1.0~1.5 (lb)	7.5
RKV 60PA			0.012~0.027	15.19~36.14	49.2~76.0	1.5~3.0 (lb)	19.4
RKV 80PA			0.021~0.050	33.26~80.39	108.5~168.5	3.0~8.0 (lb)	30.2
RKV100PA			0.035~0.081	60.78~148.3	207.6~321.9	6.0~15.0 (lb)	67.9
RKD 30PA			0.002~0.004	4.05~9.66	12.3~18.8	~1.0 (lb)	2.9
RKD 40PA			0.005~0.013	6.80~16.45	20.7~32.0	1.0~1.5 (lb)	7.5
RKD 60PA			0.012~0.027	15.19~36.14	49.2~76.0	1.5~3.0 (lb)	19.4
RKD 80PA			0.021~0.050	33.26~80.39	108.5~168.5	3.0~8.0 (lb)	30.2
RKD100PA			0.035~0.081	60.78~148.3	207.6~321.9	6.0~15.0 (lb)	67.9